

DCE-C 10/12 Trend

COMPACT INSTANTANEOUS WATER HEATER

PRODUCT-NO.: 238149

Find the perfect mixThe pleasure of water without the worries With this model, we have placed the emphasis on providing you with DHW convenience. This electronically controlled appliance is preset to a constant 55 °C. This makes it ideal for everyday use. You simply mix in cold water directly at the tap to achieve the preferred temperature that's right for you.

The main features

Compact instantaneous water heater with electronic open-loop control

Good energy efficiency thanks to 2i technology

Outlet temperature fixed at 55 °C

Individual temperature adjustment through mixing with cold water

Exceptionally slimline, compact design



DCE-C 6/8 Trend

Product-No.: 238148



| Type | DCE-C 6/8 Trend | DCE-C 10/12 Trend |
|----------|-----------------|-------------------|
| Part no. | 238148 | 238149 |

Technical data

| | | |
|-------------------|-------------|--------------|
| Rated voltage | 220 V | 220 V |
| Rated voltage 1 | 220 V | 220 V |
| Rated voltage 2 | 230 V | 230 V |
| Rated voltage 3 | 240 V | 240 V |
| Rated output | 6.0/8.0 kW | 10.0/12.0 kW |
| Rated output 1 | 6.0/8.0 kW | 10.0/12.0 kW |
| Rated output 2 | 6.6/8.7 kW | 11.0/13.1 kW |
| Rated output 3 | | 12.0/14.3 kW |
| Rated current | 27.3/36.4 A | 45.5/54.5 A |
| Rated current 1 | 27.3/36.4 A | 45.5/54.5 A |
| Rated current 2 | 28.5/38.0 A | 47.8/57.0 A |
| Rated current 3 | | 50.0/59.5 A |
| Fuse protection | 30/40 A | 50/60 A |
| Fuse protection 1 | 30/40 A | 50/60 A |
| Fuse protection 2 | 30/40 A | 50/60 A |
| Fuse protection 3 | 30/40 A | 50/60 A |
| Frequency | 50/60 Hz | 50/60 Hz |
| Frequency 1 | 50/60 Hz | 50/60 Hz |
| Frequency 2 | 50/60 Hz | 50/60 Hz |
| Frequency 3 | 50/60 Hz | 50/60 Hz |
| Phases | 1/N/PE | 1/N/PE |

| | | |
|---------------------------------|-------------------|-------------------|
| Conductivity $\sigma_{15} \leq$ | 910 $\mu S/cm$ | 910 $\mu S/cm$ |
| Resistivity $\rho_{15} \geq$ | 1100 $\Omega\ cm$ | 1100 $\Omega\ cm$ |
| IP rating | IP25 | IP25 |
| Temperature setting | 55 °C | 55 °C |
| Colour | white | white |
| Switch-on water flow rate | 1.3 l/min | 1,3 l/min |
| Height | 372 mm | 372 mm |
| Width | 217 mm | 217 mm |
| Depth | 97 mm | 97 mm |
| Weight | 2.50 kg | 2.50 kg |

Contact information

You have questions? We appreciate to help you:

Call **+27 10 001 85 47** Write an email to **info@stiebel-eltron.co.za**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.